

环保物料

主要技术参数 Main Specifications

线 数 (Poles): 02 to 06
接触电阻 (Contact resistance): $\leq 15\text{m}\Omega$
绝缘电阻 (Insulation resistance): $\geq 1000\text{M}\Omega$
额定电压 (Rated voltage): 300V AC DC
额定电流 (Rated current): 9.0A AC DC
耐 电 压 (Withstand Voltage): 1500V AC/minute
温度范围 (Temperature Range) : $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

PCB Layout

Poles	Dimensions mm	
	A	B
2	4.20	9.60
3	8.40	13.80
4	12.60	18.00
5	16.80	22.20
6	21.00	26.40

2		Wafer 针	Brass Tin 黄铜镀锡	N	
1		Housing 基座	PA66 (UL94V-0/V-2)	1	White (白色)
序号	图 号	名 称	材 料	数 量	附 注

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 网址: www.dgoonne.com 电话: 0769-85337633 邮箱: 2850175988@qq.com 传真: 0769-85392827	PART. NO: 24201AL			
				LINEAR	ANGLES					APPROVED	黎腾	2017. 06. 16	DWG. NO:
				0. 0±0. 35	X° REF±6°	DESIGNER	肖坤权	2017. 06. 16					
AO	新图面发行	2017. 06. 16	UNIT: MM	0. 00±0. 25	X° ±3°	TITLE:				REV: A0 SHEET: 1/1			
REV.	REVISION RECORD	DATE	SIZE: A4	0. 000±0. 15	X° X'±2°	DRAWN	旷淇	2017. 06. 16				4. 20mmPITCH 180° WAFER DIP TYPE	